


Model No. / Description	Spec.	Remark	Nettó ár	Bruttó ár
MAC200 Motion Activated Camera 	1. Sensor: 1.3 Mega Pixel CMOS 2. Capture Mode: Motion Activated (PIR); Time Lapse; Hybrid (Time Lapse + Motion Activated) 3. Video Resolution:1280x 720(HD Resolution, AVI) 4. Field of View: 90° 5. Motion Sensor:Detect Angle: 98°;Detect Distance:4 M 6. Capture Time: One activated capture photos for 10 seconds 7. Time Interval: Captures 10~30 frames in 10 seconds (capture rate may reduce its frames while media capacity reduced) 8. Memory Storage: Up to 32GB SDHC card 9. Power Source: Battery: 2 C Batteries; DC In: 5V 10. Battery Life: Approximately 8 months (battery life will fluctuate depending on motion activity) 11. Size (DxWxH): 100 x 100 x 57 mm 12. Weight : 300 g (without batteries and accessories) 13. Waterproof: IPx4 (safe for outdoor use) 14. OS Requirements: Microsoft Windows 98/ XP/ Vista/ Win 7	Package Contents: 1. User Manual 2. Rubber Strap x 1 3. Tree Strap x 1 4. Wall Mount (AWM100) x 1 5. NOT included 2x D cell Batteries & SD card.	67 282 Ft	85 448 Ft
Optional Accessories for MAC200				
APL200 Motion Activated Infra-RED Illuminator 	1. Sensor: Dark Brown 2. Product Size : (L)100 x (W) 100 x (H) 165mm 3. Product Weight: 303 g 4. IR Wavelength: 850nm 5. Power supply: 4XD Batteries (6V, approx. 19,080 triggers) 6. LED Power 2.5W (1.25W x 2) 7. Sensor Mode: Motion Sensor & Light Sensor 8. Motion Sensor Angle: 120° 9. Motion Sensor Range: 3m 10. Delay Time: 10S 11. Operating Temperature: -5°~40°C 12. Operating Humidity: 5%~93% 13. Waterproof: IP44 14. Batter Life: about 1 year (40 triggers per day) 15. CE, RoHS Approval"	Package Contents: 1. User Manual 2. Motion Activated Infra-RED Illuminator 3. NO 4x D cell Batteries included	27 870 Ft	35 395 Ft
PeepHole Viewer				
PHV1325 Peephole Viewer 	1. Sensor: 1.3 Mega Pixel CMOS 2. PeepHole: View Angle 190 degrees (For best results please use the peephole included) 3. LCD Screen: 2.5" TFT 4. Power Source: 2 AA Batteries (good for approx. 1500 "peeps") 5. Size (LxWxH) mm: 146 (W)x 90(H) x 30(D) 6. Weight: 0.4lbs 7. 2 models for perfect images with any standard door thickness: * Model: PHV 132512 -12 mm barrel -fits any door 35~57 mm (1.38" ~ 2.24") thick. * Model: PHV 132514 -14 mm barrel -fits any door 40~69 mm (1.57" ~ 2.72") thick	Base Flange, Tightening Tool, PeepHole, User Manual, 2 AA Batteries included	22 239 Ft	28 244 Ft
PHV-MAC Motion Activated PeepHole Camera 	1. Sensor: 1.3 Mega Pixel CMOS 2. Built in Motion Sensor 3. PeepHole: View Angle 190 degrees (For best results please use the peephole included) 4. LCD Screen: 3.0" TFT 5. Power Source: 4 AA Batteries (good for approx. TBA") 6. Micro SD slot 7. Size (LxWxH) mm: TBA 8. Weight:TBA 9. 2 models for perfect images with any standard door thickness: * Model: PHV-MAC with 12 mm barrel -fits any door 35~37 mm (1.38" ~ 2.24") thick. * Model: PHV-MAC with 14 mm barrel -fits any door 40~69 mm (1.57" ~ 2.72") thick	Base Flange, Tightening Tool, PeepHole, User Manual, 4 AA Batteries included	39 130 Ft	49 695 Ft
Optional Accessories for PHVMAC				

<p>ATH100 Weather Resistant Housing for TLC200</p> 	<p>1. Weather Resistant Housing for TLC200 2. Dimension: 125X89X54mm 3. Material: Main body: PC - Outer of Diameter of the Front Lens part : acrylic - Key & side lock: Rubber 4. Weight: 110g 5. Water resistance: IP54</p>	<p>Weather Resistant Housing</p>	<p>12 668 Ft</p>	<p>16 088 Ft</p>
---	---	---	-------------------------	-------------------------